



DUCTMATE[®]
(Europe) Ltd

G Clamp

ACCESSORIES

Universal Flange Clamp



- ◆ **Can be used in conjunction with all Rectangular Slide On Flange Systems**

Arrol Road, Wester Gourdie Industrial Estate, Dundee DD2 4TH, Scotland, UK
Tel: +44 (0)1382 622111 Fax: +44 (0)1382 621444
www.ductmate.co.uk E-mail: sales@ductmate.co.uk



Technical Data Sheet

DESCRIPTION

Universal Flange Clamp

BASIC USE

For the intermediate clamping of Slide On Flange Systems.

SPECIAL CHARACTERISTICS

Can be used in conjunction with all Rectangular Flange Systems

TECHNICAL INFORMATION

Universal Flange Clamp Formed Zinc-Coated Steel

PRODUCT GUARANTEE

All component parts of the G Clamp are guaranteed against defective material.

PACKAGING INFORMATION

**Box
Quantity**

200

**Weight
Per Box**

8.67 kg

INSTALLATION INSTRUCTIONS

- 1 Prior to the fitting of 'G' Clamps, the Ductmate Flanges should be pulled together with vice grips.
- 2 Sufficient pressure should be applied to compress the Gasket to ensure an airtight joint.
- 3 Start fitting the 'G' Clamps measuring from the corner bolt and work towards the centre of the duct at specified centres.

**Low
Pressure
Ductwork**

600 centres

**Medium
Pressure
Ductwork**

450 centres

**High
Pressure
Ductwork**

300 centres